DO NOT ENTER: /VTV/

10/01/2009 U.S. Appln. No. 10/589,079 Atty. Docket No.: 8369,036.US0000

## Amendments to the Claims

Please amend the claims according to the following listing of the claims.

- 1 25. (Canceled)
- 26. (Currently Amended) A method of forming a component, comprising:

heating an aluminum coated steel blank to an austenization temperature, eausing an increase in layer thickness;

rapidly cooling said blank;

allowing said heat treated blank to stand at room temperature for an interval of time;

heating said cooled, heat treated blank a second time to an austenization temperature greater than or equal to 850°C; and

forming said blank while heated to produce said component,

- (Previously Presented) A method according to claim 26 wherein the interval of the initial heating of said blank is in the range of 9 to 30 minutes.
- 28. (Previously Presented) A method according to claim 26 wherein the conditions of the second heat treatment are controlled so as not to increase the layer thickness of the blank.
- 29. (Previously Presented) A method according to claim 26 wherein the interval of the subsequent heating of said blank is in the range of 10 seconds to 2 ½ minutes.
- 30. (Previously Presented) A method according to claim 26 including varying the heat applied to different portions of the surface of the blank.
- (Previously Presented) A method according to claim 26 including reinforcing said blank between said separate heat treatments.
- (Previously Presented) A method according to claim 26 including maintaining said blank in a heated condition while forming.
- (New) A method according to claim 26, wherein the first heating step causes an
  increase in layer thickness of the aluminum coating.